

WIDE RANGE BETA-GAMMA GM AREA MONITOR

Model – FML-9W-GM

FEATURES:

- ON-LINE REAL-TIME MONITORING ALL PLUG-IN MODULAR
- RACK MOUNT OR WALL MOUNT
- SINGLE OR MULTI-CHANNEL
- RUGGED GM DETECTORS
- LOCAL OR OPTIONAL REMOTE MONITORING
- HIGH LEVEL ALARM, SOLID STATE, NON-CONTACTING
- RS-232 OR ETHERNET DATA DOWNLOAD FOR PC AND REMOTE DISPLAY OUTPUTS
- MICROPROCESSOR BASED DATA MEASUREMENT AND DISPLAY



FML-9W-GM ELECTRONICS
FM-9

APPLICATION:

Area monitors for use in and around nuclear reactors, hot cells, irradiators and other facilities handling radioactive materials.

DESCRIPTION:

- The FML-9W-GM incorporates a digital alarm ratemeter, power supply, alarm, amplifier, choice of rack or case, and reliable GM detector.
- With the plug-in modular construction, additional channels or functions can be added.
- GM detectors and circuit design prevent the system readings from falling even in very high fields.
- Front panel controls allow the alarm set point to be displayed.
- Alarm activation produces flashing red light on front panel and piercing intermittent 2000Hz tone.
- OPTIONAL relay is also closed (or opened) for activation of remote alarms.
- OPTIONAL stand-by battery power available.



NEMA-4X



OPTIONAL
SUBMERSIBLE PROBE



TECHNICAL ASSOCIATES
OVERHOFF TECHNOLOGY

7051 Eton Ave., Canoga Park, CA 91303
818-883-7043 (Phone) 818-883-6103 (Fax)

sales@usnuclearcorp.com

Divisions of  US NUCLEAR CORP

OTCQB - UCLE

WWW.TECH-ASSOCIATES.COM

WIDE RANGE BETA-GAMMA GM AREA MONITOR

Model – FML-9W-GM

SPECIFICATIONS:

Range:	4 decade dynamic range 0.1 mR/hr to 1 R/hr * (artificial background supplied by internal radiation source in probe) *Other ranges available to 1,000 R/hr or down to 0.01 mR/hr.
Accuracy:	+/- 10% of decade
Detector:	Energy compensated halogen quenched GM detectors, in ruggedized probe with internal radiation source. Supplied with 8ft cable. OPTIONAL: Up to 500ft. of cable. OPTIONAL High range systems use High Range GM detectors. Supplied with 8 ft. cable OPTIONAL: Up to 500ft. of cable.
Anti-Saturation:	Circuitry is incorporated to prevent readings from falling below full scale in over range conditions (tested to 1,000 R/hr).
High Voltage Output:	0 to +1500V at 200 A continuously adjustable.
Energy Dependence:	20% from 100KeV to 1.2 MeV.
Temperature:	Operating range between -30 C and 50 C; drift less than 17% per C at room temperature. 0-95% humidity non-condensing.
Readout:	User programmable.
Data Output:	RS-232 or Ethernet
Front Panel Controls:	Alarm Level Set, Display Alarm Set Point, Alarm Reset Pushbutton Power On-Off, Switch
Alarms:	Alarm level is adjustable over entire range. Alarm indicators include flashing red light and beeper.
Power:	105-125 V (or 200-240 V), 50-60 Hz. Optional 12 Volt operation. Optional standby batteries, normally under continuous charge, automatically provide power for one week in event of AC power failure.
Mounting:	Electronics are normally furnished in FM-9 case but can be furnished uncased with mounting bars for rack or NEMA-4 (hostile environment) cabinet.
Options:	Multiple channel systems. Solenoid activated check source for system calibration. Remote alarm-Audio / Visual Remote meter readout with alarm. Cable to 500 feet.



TECHNICAL ASSOCIATES
OVERHOFF TECHNOLOGY

Divisions of  US NUCLEAR CORP

OTCQB - UCLE

7051 Eton Ave., Canoga Park, CA 91303
818-883-7043 (Phone) 818-883-6103 (Fax)

sales@usnuclearcorp.com

WWW.TECH-ASSOCIATES.COM