# BETA GAMMA FLOOR MONITOR

## Model ~ BFM-1

# **FEATURES:**

- BETA, GAMMA
- 3 GM DETECTORS
- 24" WIDE COVERAGE
- FAST
- SENSITIVE
- RUGGED
- ALARM: AUDIO / VISUAL
- EASY DECONTAMINATION
- HEAVY DUTY CASTER WHEELS
- SEPARATE PROBE FOR CHECKING PERSONNEL
- POSITIONAL LEAD SHIELD TO 45°



#### **APPLICATION:**

Floor monitor with 1" lead shield that can be rotated 45° to provide detection of base boards.

## **DESCRIPTION:**

- Three thin window GM detectors to form an over-lapping uninterrupted coverage twenty-four inches wide.
- A full inch of lead shielding in all directions but down minimizes any effects of changing general background.
- The lead shield may be rotated forty-five degrees to allow the detectors to ``see" baseboards.
- The heavy- duty ball bearing casters have replaceable rubber tires should contamination be a problem.
- Built-in loudspeaker and 4-range meter contribute to speed and accuracy of system.
- A separate probe is included for checking personnel, etc.

#### SPECIFICATIONS:

Coverage: 24" full with no dead spots - overlapping detectors.

Detectors: 30 mg/cm² wall detectors. See Betas from 0.2 MeV.

Sensitivity: Betas from 0.2 MeV. halogen quenched for infinite life.

**Shield:** 1" lead, all directions except down.

Shield may be rotated 45° to see baseboards.

Additional Probe: Separate probe for individual spots, personnel, or surfaces other than floor.

**Wheels:** Ball bearing casters, replaceable tires, swivel rear caster.

**Alarm:** Speaker as well as meter readout for fast response.

**4 Ranges:** 0-500; 5,000; 50,000; 500,000 cpm; (0 - 0.2, 2, 20, 200 mR/hr).

Electronics: PUG-7-D

**Power:** (2) 9 volt batteries for 150 to 300 hours.

**DIMENSIONS & WEIGHT:** 

**Size:** 35" wide, 24" coverage. Weighs 190 lbs. (86 kg).





TECHNICAL ASSOCIATES
OVERHOFF TECHNOLOGY



7051 Eton Ave., Canoga Park, CA 91303 818-883-7043 (Phone) 818-883-6103 (Fax)

Sales@usnuclearcorp.com <u>WWW.TECH-ASSOCIATES.COM</u>