BETA – GAMMA PARTICULATE AIR MONITOR

Model ~ FM-9-ABGN

FEATURES:

- **DETECTS BETA & GAMMA PARTICULATES** INCLUDING Mo-99, Cs-137, K-40
- AIRBORNE CONCENTRATION
- INTEGRATED EXPOSURE
- HIGH SENSITIVE
- REAL TIME ALARM
- LINE OPERATED
- **PORTABLE**
- STANDARD FM-9 MODULES
- CAN DRAW AIR FROM HOOD, DUCT, ETC.
- QUICK CHANGE FILTER CARTRIDGE
- REAL TIME AIR FLOW MEASURMENT DISPLAY
- COMPUTER INTERFACE USB OR **ETHERNET**
- **DATA LOGGER BUILT-IN**



APPLICATION:

The FM-9-ABGN Air Monitors assure safety against airborne radioactivity contamination by means of constant check with alarm and record capability. It provides integrated exposure information with an optional hard copy via external printer or computer.

It is a complete system but may be expanded per need with modules of the FM-9 series.

The FM-9-ABGN is sensitive and versatile.

It may be used to monitor stack effluent down to EPA levels as well as hoods, glove box or workplace air.

DESCRIPTION:

The FM-9-ABGN uses a standard filter in TA's unique quick change, no leak holder to trap any airborne particulates. The filter is under constant surveillance via a thin window pancake detector.

Air is drawn by a regulated pump through a three-foot inlet hose and exhausted via a flow meter through another three-foot hose. These may be extended to allow monitoring of hoods, glove boxes, stacks, etc.

Time is recorded by an computer wired into the pump circuit.

The unit is completely self-contained and portable. Complete with box of 100 filters.

SPECIFICATIONS:

Sensitivity: Limit of sensitivity at 120 liters/minute air flow rate is 4 x 10⁻¹³ µCi/cc integrated over an 8 hour period, or 8 x $10^{-14} \,\mu\text{Ci/cc}$ for a 40 hour period.

This corresponds to 2 x 10⁻¹⁰ µCi/ml minute exposure equal to 0.6% of the California Safety Code Title 17 and USNRC Title 10 limit for 40 hour weekly exposure to most hazardous Beta and/or Gamma emitter in absence of Ac 227.





TECHNICAL ASSOCIATES OVERHOFF TECHNOLOGY





BETA – GAMMA PARTICULATE AIR MONITOR

Model ~ FM-9-ABGN

SPECIFICATIONS (Con't):

Detector: 2" diameter thin window GM detector Model T-1190

Sensitivity to ALL Beta-Gamma positron emitters including: Mo-99, Cs-137, K-40.

ELECTRONIC MODULES INCLUDE:

MV-5.12.24: Power Supply

MAC-9: Air Control Timer; Low Flow Alarm Flowmeter

FM-9: On Board computer with color monitor

MμP: Imbedded processor

Range: 1×10^{-13} to 1×10^{-7} µCi/cc or (Ci/m³⁾ depends on count time and flow rate.

Alarm: Settable. 2000 Hz beeper and red flasher.

Response Time: Settable 1 second to 40 hours.

Readout: 7" Color LCD monitor built-in for digital and graphic user data display.

Flow Rate: Normally set at 70 liters/min.

Mass Flow Meter: Real-Time air flow rate data feeds directly into data analyzer software and

embedded processor for highest concentration accuracy.

Power: 115V, 50-60 Hz (Optional 230 V). Shielding: 1" lead about sample and detector.

Pump: Muffler and trap included. 115V 60Hz 2A. (230 V 50-60 Hz optional).

Filters: Includes box of 100 glass fiber filters – 2" or 55mm.

Can also use membrane, paper or glass fiber filters.

Case: Electronics housed in enameled aluminum case; carrying handles optional.

WEIGHT & DIMENSIONS:

Dimensions: Excluding pump and detector assembly: 20"W x 13"H x 18" D.

Detector assembly 5"W x 10"H x 6" D. Pump assembly 8"W x 8"H x 14"D.

Shipping Weight: 84lbs.

Accessories: Filter: Free flowing glass fiber filters – 2" or 55mm.

Oil-Less Green Turtle Pump

DESCRIPTION	FM-9-ABGN
Read-Out Units Optional	μCi/cc
Read-Out Units	Specify at Time of Order
Measures	Airborne Concentration
Smart System	Calculations by Imbedded Processor On Board Data Logger
Special Feature	Electronic Mass Flowmeter











